

DECK FLOOR

INSTALLATION GUIDE FORM

Thank you for buying Flex Stone products. Prior to installation of the material, please read this form carefully.

Product Name:

Woodlike Floor Concrete Planks

GENERAL INSTRUCTIONS

- Flexstone Inc. guarantees that the products supplied by the company are in compliance with the Technical Brochure and free from defects, which makes them ideal for their intended uses, within the natural tolerances of the production process.
- Customers recognise that, due to the technical characteristics of the products they buy, there may be certain differences in the shades and optical characteristics of the product.
- Temperature and humidity changes in the manual production process used for the manufacturing of deckwood planks produced by Flexstone Inc. can cause changes in the shades of such stones. We suggest that you buy the entire required quantity, taking into account the floor from edge to edge, and use different random cartons during the installation.
- Any product inconsistency should be reported to Flexstone Inc. only in writing, within 2 days of arrival of merchandise. Any defect reports should be accompanied by all information relating to the taking over and it must be completed PRIOR to any use or application of the merchandise.
- The colours and textures of the product depicted on the company publications are as accurate photography and printing techniques allow them to be. We suggest that you see samples of the

DECK FLOOR

INSTALLATION GUIDE FORM

actual products before you buy them at point of sales. Flexstone Inc. reserves the right to make product improvements without prior notice.

- Any warranties provided by Flexstone Inc. shall no longer be valid if the recommended installation instruction are not followed faithfully. Any users who need more detailed instructions than those printed on this brochure should contact a competent salesperson or visit our website at

PREPARATIONS FOR INSTALLATION

- Do not apply Deckwood plank upon a painted surface or upon a surface covered with a film of varnish. Correct the situations, depending on the case.
- Do not apply Deckwood plank upon surfaces with an increased water absorption ratio, upon surfaces that are corroded by humidity, or upon dust – covered or flimsy surfaces.
- During installation in extreme climates, we suggest to use Latex based adhesives and

MORTARS EQUIVALENT to the specifications and RESISTANCE THAT local installation techniques require.

- Do not install the product if it is not in compliance with the specifications. Contact your supplier as soon as possible, producing the relevant purchasing invoices.

INSTALLATION PROCEDURE

- Aluminium Channels are placed at the bottom at a spacing of 18”
- Woodlike Floor Concrete Planks are glued with Latex based Adhesive and are placed on the Aluminium channels
- To give shadow impact on the Planks, FlexStone liquid colours are mixed with Flexseal and applied on the planks after installation
- The final step is to apply “Acrylic Sealers” on the planks. This is an anti skid sealer and protects the planks against all weather conditions